



3203L 32-inch

Touchscreen Signage



Up to 40 Touches



Commercial Grade



3-Year Warranty
(AUR Included)

Product Overview

Elo's 32-inch touchscreen display provides a brilliant canvas for adding interactivity to any environment. Perfect for everything from endless aisle and brand experiences to menu boards, collaborative meetings and dashboarding, the 3203L offers a sleek, slim design built to withstand the rigors of continuous commercial use. And with Elo's computer modules, you can easily turn the display into a powerful, all-in-one, life-size tablet.

Enabling up to 40 touches with fast and extremely sensitive response time and anti-friction glass to minimize heat as fingertips drag across the screen, Elo's 3203L with industry leading TouchPro® PCAP technology is designed with the user in mind. And with touch thru capability, the interactive display can be mounted behind a mirror, in a counter or in a fully encased kiosk for added durability or aesthetics.

Drive collaboration with ease by pairing the 3203L interactive display with the Elo Huddle Kit

Create an integrated solution with Elo Edge Connect accessories including - cameras, payment devices, NFC/RFID and scanners

Flexible mounting in portrait, landscape and table-top orientation

3203L 32" Touchscreen Signage

Specifications	
Model	3203L
Bezel Color	Black
Display	31.5" / 800.1 mm diagonal, active matrix TFT LCD
Active Display Area (W x H)	27.5" x 15.47" / 698.4 mm x 392.9 mm
Native Resolution	Full HD 1920 x 1080 @ 60Hz
Preset Video Timings	640x480 60Hz; 800x600 56/60Hz; 1024x768 60Hz; 1280x720 60Hz; 1280x960 60Hz; 1280x1024 60Hz; 1920x1080 50/60Hz
Touch Technology	TouchPro® PCAP - up to 40 touches with palm rejection and touch thru capability
Touch Thru	TouchPro® PCAP supports up to 6mm glass/3mm plastic with up to 2 touches. Supports gloves up to 1.4mm.
Aspect Ratio	16:9
Number of Colors	16.7 million, 8bit(D)
Brightness (typical)	LCD Panel 500 nits; with PCAP 430 nits
Response Time (Tr + Tf) (typical)	8 msec
Viewing Angle (typical)	Horizontal: ±89°/178° total; Vertical: ±89°/178° total
Contrast Ratio (typical)	3000:1
On-Screen Display (OSD)	Let's Get Started: Language Selection, Time Setting, Time Zone; Video Source Select: HDMI-1, HDMI-2, DisplayPort, USB-C, Internal-PC DP, Internal-PC HDMI; Video Settings: Video Port Discovery, Brightness, Contrast, Black Level, Sharpness and Aspect Ratio can be selected; Color Settings: Color Temperature, Color Sensor, User Preset (for color), Picture Modes and HDMI Full Range are available in this menu.; Audio Settings: Audio Input, Audio Output, Mute, Volume selection are available here.; Power: Power Loss Behavior, Power Lock, Energy Saving Mode, Power Status Light options are available here; Time: Time Set, On/Off Schedule; OSD Settings: Recall Defaults, OSD Timer, OSD Language, OSD Lock and OSD Portrait Rotation, Touch Switch, Tabletop; Information: Monitor, Temperature, Help and Support are available here; See user manual for full details.
I/O Ports	HDMI 1.4 x2, USB-C (for Touch and Video), RJ45 (for optional OSD remote), DisplayPort 1.2, 3.5mm TRS jack (for RS232), 3.5mm Audio Headphones out, Micro USB 2.0 x4
Control Buttons	Power Button, Video Source Selection Button, On Screen Display Button
Video	2x HDCP-capable HDMI on Type A connector, DisplayPort 1.2 connector; USB-C connector; Input Video Horizontal Sync frequency range: FHD: 30 - 69 KHz; Input Video Vertical Sync (frame rate) frequency range: 24 - 64 Hz
Power	Input connector (power): IEC 60320-C13; Input signal specifications (power): 100-240VAC 50/60Hz Monitor + AC/DC adapter: ON: 44W; SLEEP: 1.43; OFF: 0.29W Monitor with ECMG4 + AC/DC adapter: ON: 81W; SLEEP: 3.5W
Audio	Speakers: 2 x 5 W stereo speakers; Headphone output: 3.5 mm TRS jack
Mounting Options	VESA 400 x 400mm
Dimensions	30.11" x 18.07" x 2.25" / 764.7 mm x 459.1 mm x 57.2 mm
Shipping Dimensions	35.04" x 25.2" x 6.3" / 890 mm x 640 mm x 160 mm
Weight	Unpackaged - With ECMG4: 30.8 lbs / 13.97 Kg; Without ECMG4: 26.17 lbs / 11.87 Kg; Packaged - Without ECMG4: 33.75 lbs / 15.31 Kg
Maximum Operating Time	24 hours/day
Other Features	Ambient Light Sensor - changes panel color to match ambient light, Auto Wake
MTBF	50,000 hours demonstrated
Temperature	Portrait/Landscape/Tilt (≤15°) Mode - Operating: 0° C to 40° C / 32° F to 104° F; Storage: -20° C to 60° C / -4° F to 140° F Tabletop Mode - Operating: 0° C to 35° C / 32° F to 95° F; Storage: -20° C to 60° C / -4° F to 140° F
Humidity (non-condensing)	Operating: 20% - 80%; Storage: 10% - 90% (38.7° C max wet bulb temperature)
Regulatory Approvals and Declarations	UL 62368-1; FCC (US); cUL, IC (Canada); CB (International safety) (IEC/EN60950-1+IEC/EN62368-1); CE (Europe); VCCI (Japan); RCM (Australia); CCC, China RoHS (China) (for TouchPro version only); EAC (Russia); NOM (Mexico); IK07 and UL60950 for ball drop test
Compliance	Energy Star 8.0
Warranty	3 years standard with AUR included
Extended Warranty	4 year + AUR - Elo P/N: E740135; 5 year + AUR - Elo P/N: E740330; 3 year + OSE (Continental US Only) - Elo P/N: E740527 4 year + OSE (Continental US Only) - Elo P/N: E740728; 5 year + OSE (Continental US Only) - Elo P/N: E740918
What's in the Box	Quick Install Guide; HDMI 2.0 cable (Type A plug to Type A plug); USB cable (Type A plug to Type C plug); Power cable, IEC 60320-C13 to NA plug; Power cable, IEC 60320-C13 to EU/KR plug; Power cable, IEC 60320-C13 to UK plug; Serial 3.5mm male to Serial DB9 female cable; Energy label according to EU Regulation 1062/2010

Ordering Information

Part Number	Technology	Surface Treatment	Touch Interface
E720061	TouchPro PCAP	Clear with Anti-Friction	USB-C

Optional Computer Modules

Model	Part Numbers	Processor	RAM	Storage	OS
ECMG4-i5	E227895	Intel Core i5-7500 Processor	8GB	256GB SSD	No OS
	E725044	Intel Core i5-7500 Processor	8GB	256GB SSD	Windows 10 SAC
	E228087	Intel Core i5-7500 Processor	8GB	256GB SSD	Windows 10 LTSC
	E898841	Intel Core i5-7500 Processor	8GB	256GB SSD	Windows 10 LTSC with Montage Software
	E405488	Intel Core i5-7500 Processor	16GB	256GB SSD	Windows 10 SAC with Whiteboard Software & 30 day trial Montage & Launcher Software
Elo Backpack®	E611864	Qualcomm Snapdragon APQ8053 CPU	2GB	16GB eMMC	Android 7.1
	E901355	Qualcomm Snapdragon APQ8053 CPU	2GB	16GB eMMC	Android 8.1

Learn more about Elo at [EloTouch.com](https://elotouch.com).

Americas

Tel +1 408 597 8000
elosales.na@elotouch.com

Europe (EMEA)

Tel +32 16 930 136
EMEA.Sales@elotouch.com

Asia Pacific

Tel +86 (21) 3329 1385
EloAsia@elotouch.com

Elo reserves the right to change or update, without notice, any information contained herein; to change, without notice, the design, construction, materials, processing or specifications of any products; and to discontinue or limit production or distribution of any products. Elo, the Elo logo, Elo Backpack and TouchPro are either trademarks or registered trademarks of Elo Touch Solutions, Inc. All other trademarks are the property of their respective owners.
© 2023 Elo Touch Solutions, Inc. All rights reserved. 23041AES00144

