Getac








K120 FULLY Rugged tablet

- 11th Generation Intel[®] Core™ i7 / i5 vPro[®] Processor
- 12.5" FHD LumiBond[®] display with Getac sunlight readable technology (1,200 nits) and capacitive touchscreen
- Enhanced enterprise security with optional Intel[®] vPro[®] , Windows Hello face-authentication camera, and multifactor authentication options
- Multi-mode usage streamlined by extensive accessory selections
- LifeSupport[™] battery swappable technology
- Thunderbolt™ 4 brings lightning speed and performance



SPECIFICATIONS

Generation G2-R

Operating System Windows 11 Pro

Mobile Computing Platform

Intel[®] Core™ i5-1135G7 Processor Max. 4.2GHz with Intel[®] Turbo Boost Technology - 8MB Intel[®] Smart Cache

Platform options: Intel[®] Core™ i5-1145G7 vPro[®] Processor Max. 4.4GHz with Intel[®] Turbo Boost Technology - 8MB Intel[®] Smart Cache

Intel[®] Core™ i7-1165G7 Processor Max. 4.7GHz with Intel[®] Turbo Boost Technology - 12MB Intel[®] Smart Cache

Intel[®] Core™ i7-1185G7 vPro[®] Processor Max. 4.8GHz with Intel[®] Turbo Boost Technology - 12MB Intel[®] Smart Cache

VGA Controller Intel[®] Iris[®] X^e Graphics

Display 12.5" Wide Viewing Angle TFT LCD FHD (1920 x 1080) 1,200 nits LumiBond[®] display with Getac sunlight readable technology Capacitive multi-touch screen

Storage & Memory 16GB DDR4

Optional: 32GB / 64GB DDR4

256GB PCIe NVMe SSD Optional: 512GB / 1TB / 2TB PCIe NVMe SSD

Keyboard

Power button 5 tablet programmable buttons

Pointing Device

Touchscreen · Capacitive multi-touch screen · Optional: Dual mode touchscreen (multi-touch and digitizer)

Expansion Slots Optional: 1D/2D imager barcode reader Optional: Serial port (9-pin; D-sub), or USB 2.0 port

I/O Interfaces

Tablet Tablet FHD webcam x 1 ⁱⁱ 8M pixels auto focus rear camera x 1 Audio in/out combo x 1 DC in Jack x 1 USB 3.2 Gen 2 Type-A x 1 ThunderboltTM 4 Type-C x 1 LAN (RJ-45) x 1 HDMI 2.0 x 1 Docking connector x 2 Optional: SIM card slot x 1 (Micro-SIM, 3FF)^{III} Optional: Windows Hello face-authentication camera (front-facing) x 1^{III} (front-facing) x 1[®] Optional: RF antenna pass-through for GPS, WWAN and WLAN Optional keyboard dock: Optional Reyboard dock: DC in Jack x 1 USB 3.2 Gen 1 Type-A x 3 LAN (RI45) x 1 HDMI 2.0 x 1 Display port 1.2 x 1 Serial port (9-pin; D-sub) x 1 Optional: RF antenna pass-through for GPS, WWAN and WLAN

Communication Interface

10/100/1000 base-T Ethernet Intel[®] Wi-Fi 6 AX201, 802.11ax Bluetooth (v5.2) ^{iv} Optional: Dedicated GPS ` Optional: 4G LTE mobile broadband with integrated GPS v

Optional: 5G Sub-6 with integrated GPS xix, xo

Security Features

Security reduces TPM 2.0 Kensington lock Optional: Intel[®] vPro[®] Technology Optional: Smart card reader or HF RFID reader ^{v(,viii} or Fingerprint reader ⁱⁿ Optional: Windows Hello face-authentication camera (front-facing) ⁱⁱ

Power

AC adapter (90W, 100-240VAC, 50/60Hz) Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2 LifeSupport™ battery swappable technology Optional: High capacity Li-ion battery (14.4V, typical 3450mAh; min. 3300mAh) x 2

Dimension (W x D x H) & Weight

Tablet 329.5 x 238 x 24mm (12.97" x 9.37" x 0.94") 1.7kg (3.75lbs) *

Tablet + Optional keyboard dock: 340.5 x 307.5 x 47mm (13.40" x 12.10" x 1.85") 3.13kg (6.9lbs) ^x

Rugged Features MIL-STD-810H certified IP66 certified IP66 certified MIL-STD-461G certified ^{xi} Vibration & 6ft (1.8m) drop-resistant ^{xii} Optional: ANSI/UL 121201, CSA C22.2 NO. 213 (Class I, Division 2, Groups A, B, C, D) ^{xiii}

Environmental Specifications

Temperature ^{xiv}: - Operating: -29°C to 63°C / -20°F to 145°F - Storage: -51°C to 71°C / -60°F to 160°F Humidity: - 95% RH. non-condensing

Pre-installed software

Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager[™] Getac Driving Safety Utility (trial version) Getac KeyWedge Barcode Reader Utility (trial version) Optional: Absolute Persistence®

Optional software

Getac Driving Safety Utility Getac KeyWedge Barcode Reader Utility Getac Device Monitoring System (GDMS) Getac VGPS Utility ^{xil}

| | Vehicle Dock for Tablet Mode | Vehicle Dock for Laptop Mode | Office Dock for Tablet Mode | Office Dock for Laptop Mode |
|----------------------|----------------------------------|----------------------------------|-----------------------------------|----------------------------------|
| Serial Port | 1 | 1 | 1 | 1 |
| VGA | 1 | 1 | 1 | 1 |
| Microphone | - | - | 1 | 1 |
| Audio Output | - | - | 1 | 1 |
| DC in Jack | 1 | 1 | 1 | 1 |
| USB | USB 2.0 x 3 USB 3.2 Gen 1 x 3 | USB 2.0 x 3 USB 3.2 Gen 1 x 3 | USB 2.0 x 2 USB 3.2 Gen 1 x 3 | USB 2.0 x 2 USB 3.2 Gen 1 x 3 |
| LAN | 2 | 2 | 2 | 2 |
| HDMI 2.0 | 1 | 1 | 1 | 1 |
| RF Antenna Connector | 3 (WWAN, WLAN, GPS) | 3 (WWAN, WLAN, GPS) | - | - |
| Kensington Lock | 1 | 1 | 1 | 1 |

K120 FULLY **RUGGED TABLET**

Accessories Battery (11.1V, typical 2100mAh; min. 2040mAh) AC adapter (90W, 100-240VAC) Capacitive stylus with tether

Optional:

Optional: Carry bag Battery (11.1V, typical 2100mAh; min. 2040mAh) High capacity Li-ion battery (14.4V, typical 3450mAh; min. 3300mAh) Multi-Bay charger (Dual-Bay) Multi-Bay charger (Eight-Bay) AC adapter (90W, 100-240VAC) Office dock AC adapter (120W, 100-240VAC) MIL-STD-461 AC adapter (90W, 100-240VAC) DC-DC vehicle adapter (120W, 11-32VDC) Divitivar neg Digitizer pen Capacitive stylus with tether Protection film Hard handle Hard handle Rotating hand strap with kickstand Shoulder strap (2-point) Shoulder harness (4-point; handsfree) Vehicle cradle Keyboard dock Vehicle dock ^{xvii,} Office dock Spare SSD kit 100W Type-C adapter Getac rugged keyboard

Bumper-to-Bumper Warranty

Bumper-to-Bumper Warranty Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime. That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days. Standard Standard

3 years Bumper-to-Bumper

- Units equipped with dual channel memory come with Intel[®] Iris[®] X^c Graphics.
 FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually exclusive option. П.
- options. Units with 4G LTE option comes with an embedded SIM card III.
- Units with 4G LTE option comes with an embedded SIM card slot. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area. Dedicated GPS is mutually exclusive with 4G LTE mobile broadband. Supports GPS and Glonass. Units with 4G LTE option comes with an embedded SIM card slot. IV.
- V.
- VI.
- VII.
- Units with 4G LTE option comes with an embedded SIM card slot. 13.56MHz HF RFID/NFC reader (ISO 15693, 14443 A/B, Mifare and FeliCa^{TW} compliant). LF/HF RFID reader option is not Energy Star 8.0 compliant. Smart card reader, HF RFID reader and Fingerprint scanner are mutually exclusive options. Weight and dimensions vary from configurations and optional accessories; optional high capacity batteries add approx. 11mm (H), 0.20kg. MIL-STD-461 90W AC adapter sold separately. Drop test results vary from configurations and optional accessories. VIII. IX.
- Χ.
- accessories. Available with limited configurations and environment XIII.
- conditions. Tested by an independent third-party test lab following MIL-STD-810H. Available when barcode reader option is selected. XIV.
- XV.
- XVI. XVII. XVIII. XIX.
- Available when barcode reader option is selected.
 XVI. Models require either embedded or standalone GPS module.
 XVII. Gamber Johnson and Havis vehicle docks are e-mark certified.
 XVIII. Available for laptop and tablet mode.
 XIX. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers.
 XX. Support GPS, GLONASS, Galileo, BeiDou and QZSS.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.





Getac (UK) Ltd.

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel : +44 (0) 1952 207 222 Sales-Getac-UK@getac.com I www.getac.com/en/ Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.





K120-EX FULLY RUGGED TABLET

- ATEX/IECEx Zone2/22 certified for hazardous locations
- 11th Generation Intel[®] Core[™] i7 / i5 vPro[®] Processor
- 12.5" FHD LumiBond[®] display with Getac sunlight readable technology (1,200 nits)
- Enhanced enterprise security with optional Intel vPro, Windows Hello face-authentication camera and multifactor authentication options





SPECIFICATIONS

Generation G2-R

Operating System Windows 11 Pro

Mobile Computing Platform

Intel[®] Core™ i5-1135G7 Processor Max. 4.2GHz with Intel[®] Turbo Boost - 8MB Intel[®] Smart Cache

Platform options:

Intel[®] Core[™] i5-1145G7 vPro[®] Processor Max. 4.4GHz with Intel[®] Turbo Boost - 8MB Intel[®] Smart Cache

Intel[®] Core™ i7-1165G7 Processor Max. 4.7GHz with Intel® Turbo Boost Technology - 12MB Intel[®] Smart Cache

Intel[®] Core[™] i7-1185G7 vPro[®] Processor Max. 4.8GHz with Intel® Turbo Boost Technology - 12MB Intel[®] Smart Cache

VGA Controller

Intel[®] Iris[®] X^e Graphics

Display 12.5" Wide Viewing Angle TFT LCD FHD (1920 x

1,200 nits LumiBond[®] display with Getac sunlight readable technology

Storage & Memory 16GB DDR4

Optional: 32GB / 64GB DDR4

256GB PCIe NVMe SSD Optional: 512GB / 1TB / 2TB PCIe NVMe SSD

Keyboard Power button 5 tablet programmable buttons

Pointing Device

Touchscreen Dual mode touchscreen (multi-touch and digitizer)

Expansion Slots Optional: 1D/2D imager barcode reader Optional: Serial port (9-pin; D-sub), or USB 2.0 port

I/O Interfaces

FHD webcam x 1 8M pixels auto focus rear camera x 1 Audio in/out combo x 1 DC in Jack x 1 USB 3.2 Gen 2 Type-A x 1 Thunderbolt™ 4 x 1 LAN (RJ-45) x 1 HDMI 2.0 x 1 Optional: SIM card slot x 1 (Micro-SIM, 3FF) ⁱⁱ Optional: Windows Hello face-authentication camera (front-facing) x 1

Communication Interface 10/100/1000 base-T Ethernet Intel[®] Wi-Fi 6 AX201, 802.11ax Bluetooth (v5.2) Optional: Dedicated GPS ^{iv} Optional: 4G LTE mobile broadband with integrated GPS Optional: 5G Sub-6 with integrated GPS xii, xiii

Security Features

TPM 2.0 Kensington lock Optional: Intel[®] vPro[®] Technology Optional: Smart card reader or HF RFID reader vi Optional: Windows Hello face-authentication camera (front-facing)

Power

AC adapter (90W, 100-240VAC, 50/60Hz) Li-ion battery (11.1V, typical 2100mAh; min. 2040mAh) x 2

Dimension (W x D x H) & Weight 329.5 x 238 x 24mm (12.97" x 9.37" x 0.94")

1.76kg (3.88lbs)

Rugged Features MIL-STD-810H certified

IP66 certified Vibration & 6ft (1.8m) drop resistant viii ATEX & IECEx certified

Environmental Specifications

Temperature $^{\rm ix}$: - Operating: -29°C to 63°C / -20°F to 145°F - Storage: -51°C to 71°C / -60°F to 160°F

Humidity :

- 95% RH, non-condensing

Explosion Protection

ATEX/IECEx Zone 2/22 Ex II 3G Ex ic op is IIC T4 Gc Ex II 3D Ex ic op is IIIB T130°C Dc

Pre-installed software Getac Utility Getac Camera Getac Geolocation Getac Barcode Manager^{*} Getac Driving Safety Utility (trial version) Getac KeyWedge Barcode Reader Utility (trial version)

Optional: Absolute Persistence®

Optional software

Getac Driving Safety Utility Getac KeyWedge Barcode Reader Utility Getac Device Monitoring System (GDMS) Getac VGPS Utility

Accessories

Battery (11.1V, typical 2100mAh; min. 2040mAh) AC adapter (90W, 100-240VAC) Digitizer pen

Optional:

Battery (11.1V, typical 2100mAh; min. 2040mAh) Multi-Bay charger (Dual-Bay) Multi-Bay charger (Eight-Bay) AC adapter (90W, 100-240VAC) Diaitizer pen Anti-static protection film Rotating hand strap with kickstand Shoulder strap (2-point) Spare SSD kit

Bumper-to-Bumper Warranty Accidents can take your equipment out of service when you least expect it, especially in a rugged environment, which can cause costly equipment downtime. That is why Getac has introduced accidental damage as standard under our Bumper-to-Bumper warranty, to help minimize your enterprise IT costs. Bumper-to-Bumper is your hassle-free guarantee. That means you can depend on us to have your unit back in service within days.

Standard

3 years Bumper-to-Bumper

K120-EX FULLY **RUGGED TABLET**

- FHD webcam and optional Windows Hello face-authentication camera (front-facing) are mutually I.
- П. Ш.
- authentication camera (front-facing) are mutually exclusive options. Units with 4G LTE option comes with an embedded SIM card slot. Bluetooth performance and connectable distance may be subject to interference with the environments and performance on client devices, users may be able to reduce effects of interference by minimizing the number of active Bluetooth wireless devices that is operating in the area. Dedicated GPS is mutually exclusive with 4G LTE mobile broadband. Supports GPS and Glonass. Units with 4G LTE option comes with an embedded SIM card slot. Smart card reader and HF RFID reader are mutually exclusive options.
- IV. V.
- VI.
- exclusive options. Weight and dimensions vary from configurations and optional accessories. Drop test results vary from configurations and VII.
- VIII.
- IX.
- optional accessories. Tested by an independent third-party test lab following MIL-STD-810H. Available when barcode reader option is selected. Models require either embedded or standalone GPS module. X. XI.
- module. XII. One physical SIM card slot and one eSIM. Network service may vary depending on local telecommunication providers. XIII. Support GPS, GLONASS, Galileo, BeiDou and QZSS.

Information provided herewith is for reference only, available specification shall be subjected to quotation by request.

Getac

Getac House, Stafford Park 12, Telford, Shropshire TF3 3BJ, United Kingdom Tel : +44 (0) 1952 207 222 Sales-Getac-UK@getac.com I www.getac.com/en/ Copyright © 2022 Getac Technology Corporation and/or any of its affiliates. All Rights Reserved. Information provided herewith is for reference only, available specification shall be subjected to quotation by request.