

# SUNMI D2s PLUS Smart Desktop Terminal

New

Better printing performance, and more.

Powered by  
**SUNMI OS**



## A more powerful printer inside.

A desktop terminal that prints at 250mm/s\* definitely will be your great helper at peak hours. The 80mm wide receipts give you more room for your creative ideas that show your brand personality, no matter by long texts or images, or combined.

## A printer that "feels" smoothes your business operations.

The newly added sensors for paper jam, paper pickup, out of paper and overheated motor can effectively protect the printer and also delivers smooth receipt printing experience.

## More configuration options.

Three display options. Find what combination works best for you.

## Display Options

15.6"

Single 15.6"FHD,1920\*1080

15.6" + 10.1"

Main 15.6"FHD,1920\*1080  
Secondary 10.1"HD, 1024\*600

15.6" + 15.6"

Main 15.6"FHD,1920\*1080  
Secondary 15.6"FHD,1920\*1080





## SUNMI D2s PLUS Specs

### Model Approved

L1584  
L1585  
L1586

### OS

Android 11  
SUNMI OS

### CPU

RK 3568 Cortex-A55  
Processor 2.0GHz

### Memory

2GB RAM + 16GB ROM

### Speaker

1\* 3W

### Display

Config 1:  
Main: 15.6" FHD, 1920\*1080 Capacitive multi-touch screen  
Config 2:  
Main: 15.6" FHD, 1920\*1080 Capacitive multi-touch screen  
Secondary: 10.1" HD, 1024\*600 Capacitive multi-touch screen  
Config 3:  
Main: 15.6" FHD, 1920\*1080 Capacitive multi-touch screen  
Secondary: 15.6" FHD, 1920\*1080 Capacitive multi-touch screen

### Printer

Built-in 80mm thermal printer  
Print speed: 250mm/s  
Service life: 150km  
Max paper roll diameter: 80mm

### Ports

5\* USB Type A port  
1\* RJ11 port  
1\* RJ12 cash drawer port  
1\* RJ45 LAN  
1\* 3.5mm audio jack  
1\* Power port  
1x Micro-USB debug port

### Bluetooth

Support Bluetooth 5.0  
Support BLE

### Ethernet

LAN 100M

### Button

1\* Power (lock screen) key

### External Memory Card

1\* MicroSD (TF)  
Up to 1TB

### Wi-Fi

IEEE 802.11 a/b/g/n/ac  
2.4 & 5 GHz dual band

### Power Adapter

Input: AC100~240V/1.7A  
Output: DC24V/2.5A

### Dimensions (L\*W\*H)

Config 1: 381.73\*331.6\*498.03mm  
Config 2: 381.73\*349.08\*498.52mm  
Config 3: 381.73\*369.61\*525.52mm

### Weight

Config 1: 7.0kg  
Config 2: 7.770kg  
Config 3: 8.695kg

### Environment

Working temp.: 0°C~40°C  
Storage temp.: -20°C~60°C

1.The usable memory may be less than the installed memory.  
2.All specifications are subject to change without (prior) notice.